

POOL SAND FILTER

Fiberglass Sand Filter

“ **OCEAN** ”

Side mount sand filter are built to be tougher, longer lasting and better performing. Constructed of polyester resin and non-corrosive fiberglass filament winding, all internal components and connections are injection molded PVC. UV-resistance surface allows working under sunshine. Easy-to-use six-position valve makes you select any of the valve/filter operation in a proper way.





EXPERIENCE ... since 1988

POOL SAND FILTER

Fiberglass Sand Filter

“ OCEAN ”



ØD(mm)	450	535	635	710	750	800	900	1000	1100	1200	1400
H(mm)	670	710	810	880	980	1010	1100	1160	1260	1340	1570
A(mm)	260	290	310	360	385	385	430	540	540	540	700
B(mm)	75	75	95	90	120	150	150	150	180	180	180
C(mm)	125	125	125	125	220	220	220	220	220	220	220
M(mm)	440	460	490	540	680	680	725	835	835	835	995
ØP(mm)	390	390	565	565	565	790	790	790	1010	1010	1010
T(mm)	250	280	300	350	400	420	480	510	560	600	630

Product Parameters

Model	Pipe Size		Filter Area(m ²)	Design Flow		0.5-0.8mm Sand Weight (kg)	Tank Volume (m ³)	Valve Volume (m ³)	Tank Diameter (mm)	Tank Height (mm)
	inches	mm		m ³ /h	lpm					
WL-BCG450	1.5	50	0.16	8	133	50	0.15	0.02	450	670
WL-BCG500	1.5	50	0.23	11.5	192	80	0.2	0.02	535	710
WL-BCG650	1.5	50	0.32	16	267	160	0.32	0.02	635	810
WL-BCG700	1.5	50	0.4	20	333	220	0.42	0.02	710	880
WL-BCG750	2	63	0.44	22	367	230	0.44	0.02	750	980
WL-BCG800	2	63	0.5	25	417	260	0.68	0.02	800	1010
WL-BCG900	2	63	0.64	30	533	400	0.92	0.02	900	1100
WL-BCG1000	2	63	0.79	35	645	600	1.48	0.02	1000	1160
WL-BCG1100	2	63	0.95	44	716	800	1.98	0.02	1100	1260
WL-BCG1200	2	63	1.13	50	850	920	2.42	0.02	1200	1340
WL-BCG1400	2	63	1.53	68	1133	1400	3.26	0.02	1400	1570

PISCINE

Products Sponsored By

SAMAR AGUA S.L PISCINE

Madrid – Spain

WWW.PISCINE.ES